



SIZE	CODE	DIMENSIONS		
	BSP	B	A	KG EACH
1/8	CTN02	23mm	10.3	0.011
1/4	CTN04	24mm	13.7	0.017
3/8	CTN06	25mm	17.2	0.023
1/2	CTN08	29mm	21.3	0.038
3/4	CTN12	32mm	26.7	0.053
1	CTN16	38mm	33.4	0.094
1-1/4	CTN20	38mm	42.2	0.124
1-1/2	CTN24	44mm	48.3	0.162
2	CTN32	44mm	60.3	0.231
2-1/2	CTN40	57mm	76.1	0.379
3	CTN48	64mm	88.9	0.539
4	CTN64	76mm	114.3	0.93

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.

