



SIZE	CODE		DIMENSIONS		
	BSP	NPT	A	B	KG EACH
1/8	SP02	SP02N	7	15.5	0.02
1/4	SP04	SP04N	8	19	0.02
3/8	SP06	SP06N	9	18	0.02
1/2	SP08	SP08N	10	18.5	0.02
3/4	SP12	SP12N	14	21	0.03
1	SP16	SP16N	17	24	0.06
1-1/4	SP20	SP20N	20	28	0.10
1-1/2	SP24	SP24N	23	28	0.12
2	SP32	SP32N	28	34	0.20
2-1/2	SP40	SP40N	36	38.5	0.35
3	SP48	SP48N	40	41.5	0.52
4	SP64	SP64N	52	51.5	0.93

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Square Head Plugs are available threaded BSPT and NPT.

They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Did you know, we also keep Plugs with a hexagon head?

