





SIZE	PRODUCT CODE	PRODUCT CODE	DIMENSIONS			KG EACH
SILE	BSPT	NPT	A (MIN)	B (MIN)	C (MIN)	NG EACH
1/8	3SP02T	3SP02N	10	6	7.15	0.01
1/4	3SP04T	3SP04N	11	6	9.55	0.02
3/8	3SP06T	3SP06N	13	8	11.11	0.03
1/2	3SP08T	3SP08N	14	10	14.29	0.05
3/4	3SP12T	3SP12N	16	11	15.88	0.08
1	3SP16T	3SP16N	19	13	20.64	0.16
1-1/4	3SP20T	3SP20N	21	14	23.81	0.27
1-1/2	3SP24T	3SP24N	21	16	28.58	0.38
2	3SP32T	3SP32N	22	18	33.27	0.63

^{**} DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Square Head Plugs are available in BSPT and NPT configurations - ASME B16.11-2016

Pressure rating up to 400 BAR (6000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1 NPT threads are to ANSI B2.1

Larger sizes are available upon request

Hex and Square Plugs can also be supplied as part of our low pressure 150lb range





We also keep Plugs with a Hexagonal Head in 6000lb 316/L









