



SIZE	CODE		THREAD	DIMENSIONS				
	BSP	NPT		A	B	C	D	KG EACH
1/8	HT02	-	1/8	13.9	34.9	3.5	20	0.02
3/16	HT03	-	1/8	13.9	40	5	25	0.03
1/4	HT04	HT04N	1/4	15	38	6.3	20	0.03
5/16	HT05	HT05N	1/4	14.5	47.2	8	29.2	0.03
3/8	HT06	HT06N	3/8	19	51.5	9.53	32	0.06
1/2	HT08	HT08N	1/2	23.2	63	12.7	38.5	0.06
5/8	HT10	HT10N	1/2	23.2	63	16	38.8	0.06
3/4	HT12	HT12N	3/4	29	66	19.05	38	0.10
1	HT16	HT16N	1	34.8	71	25.4	42.2	0.21
1-1/4	HT20	HT20N	1-1/4	45	77.8	31.8	46	0.25
1-1/2	HT24	HT24N	1-1/2	48.6	75	38.1	55	0.38
2	HT32	HT32N	2	61.3	96.2	50.8	59.5	0.61
2-1/2	HT40	HT40N	2-1/2	78.5	116.5	63.5	72	0.93
3	HT48	HT48N	3	93.5	128	76.2	80.6	1.39
4	HT64	HT64N	4	118.5	138	101.6	84	2.23

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Male Hosetails are available threaded BSPT and NPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

Did you know we keep Reducing Hose Tails too?



TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★ CUSTOMER SERVICE



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK