



SIZE	CODE BSP	DIMENSIONS				
		A	B	C	D	KG EACH
1/4 x 1/8	RT0402	13.5	17.2	17	15.3	0.04
3/8 x 1/4	RT0604	17	19.1	21.4	20.2	0.06
1/2 x 1/4	RT0804	17.5	19	25.4	21.5	0.06
1/2 x 3/8	RT0806	21.4	20.5	25.4	21.9	0.07
3/4 x 3/8	RT1206	21.4	21.5	30.9	24.6	0.09
3/4 x 1/2	RT1208	25.4	24	30.9	27.7	0.10
1 x 1/2	RT1608	25.4	26	37.9	31.1	0.14
1 x 3/4	RT1612	30.9	29	37.9	32.1	0.16
1-1/4 x 1/2	RT2008	30.9	31	47.4	36.5	0.23
1-1/4 x 3/4	RT2012	30.9	34.5	47.4	39	0.26
1-1/4 x 1	RT2016	37.9	31.5	53.2	39.4	0.26
1-1/2 x 3/4	RT2412	30	31.5	53.2	39.4	0.26
1-1/2 x 1	RT2416	37.9	35	53.2	41.9	0.30
1-1/2 x 1-1/4	RT2420	47.4	39.5	53.2	44.4	0.35
2 x 1/2	RT3208	25.4	35.5	65.7	45.3	0.38
2 x 3/4	RT3212	30.9	35.5	65.7	45.3	0.40
2 x 1	RT3216	37.9	39	65.7	47.8	0.44
2 x 1-1/4	RT3220	47.4	43.5	65.7	50.3	0.50
2 x 1-1/2	RT3224	53.2	46.5	65.7	50.3	0.52

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Reducing Tee's are available threaded BSPP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.

