



SIZE	CODE		DIMENSIONS			
	BSP	NPT	A	B	C	KG EACH
1/8	SE02	SE02N	14.5	15.4	23	0.02
1/4	SE04	SE04N	18	17.6	27	0.04
3/8	SE06	SE06N	22	20.5	30	0.06
1/2	SE08	SE08N	27.5	23.5	36	0.07
3/4	SE12	SE12N	33.7	27	41	0.11
1	SE16	SE16N	40	31	48	0.18
1-1/4	SE20	SE20N	49	37	54.5	0.31
1-1/2	SE24	SE24N	55	41	60	0.37
2	SE32	SE32N	68	51.5	73	0.71
2-1/2	SE40	SE40N	85.9	62.5	87	1.08
3	SE48	SE48N	101	79.3	106.5	2.05
4	SE64	-	131.5	100.5	126.3	3.29

Not the elbow you are looking for? see below for more options



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK