



SIZE	CODE		DIMENSIONS		
	BSP	NPT	A	B	KG EACH
1/8	HN02	HN02N	10	29.5	0.02
1/4	HN04	HN04N	14.6	28	0.02
3/8	HN06	HN06N	18.1	31	0.03
1/2	HN08	HN08N	22.4	33.5	0.05
3/4	HN12	HN12N	28	38	0.08
1	HN16	HN16N	35	41.5	0.12
1-1/4	HN20	HN20N	44	48.5	0.19
1-1/2	HN24	HN24N	50	48.5	0.22
2	HN32	HN32N	62	57	0.33
2-1/2	HN40	HN40N	78	67	0.51
3	HN48	HN48N	91	75	0.73
4	HN64	HN64N	116	81	1.18

\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Hex Nipples are available threaded BSPT and NPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
 Note 2 Temperatures indicated are those of the Internal fluid  
 Note 3 Piping loads, stresses And moments are not taken into account

Did you know we keep hexagon nipples with mixed threads too?



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK