


## 150LB PTFE FLAT SEAT UNION 316





SIZE	CODE	DIMENSIONS		
	BSP	Α	В	KG EACH
1/8	UF02	29.1	32	0.08
1/4	UF04	29.1	33	0.10
3/8	UF06	34	35.5	0.13
1/2	UF08	37.5	37.8	0.15
3/4	UF12	44.5	41	0.20
1	UF16	53.5	49	0.37
1-1/4	UF20	64	52	0.48
1-1/2	UF24	71.5	56.3	0.66
2	UF32	85.5	63	0.95

<sup>\*\*</sup> DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Female x Female PTFE Unions are available threaded BSPP.

They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1 NPT threads are to ANSI B2.1 Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING				
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)			
-20 to 40	20			
100	16.5			
150	15			
200	14			
220	13.5			

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation metho-

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into accoun







SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM



