



SIZE	CODE		DIMENSIONS		
	BSP	NPT	A	B	Kg/100
1/8	HN02	HN02N	10	29.5	0.02
1/4	HN04	HN04N	14.6	28	0.02
3/8	HN06	HN06N	18.1	31	0.03
1/2	HN08	HN08N	22.4	33.5	0.05
3/4	HN12	HN12N	28	38	0.08
1	HN16	HN16N	35	41.5	0.12
1-1/4	HN20	HN20N	44	48.5	0.19
1-1/2	HN24	HN24N	50	48.5	0.22
2	HN32	HN32N	62	57	0.33
2-1/2	HN40	HN40N	78	67	0.51
3	HN48	HN48N	91	75	0.73
4	HN64	HN64N	116	81	1.18

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Did you know we keep hexagon nipples with mixed threads too?



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK