



SIZE BSPB (G)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	D	KG EACH
1/8	TM02	350	22.2	22.2	8	3.5	0.03
1/4	TM04	350	22.2	22.2	11	4.7	0.06
3/8	TM06	350	25.4	25.4	12	8.1	0.09
1/2	TM08	315	30.5	30.5	14	11.1	0.15
3/4	TM12	250	38.1	38.1	16	16.6	0.21
1	TM16	200	44.4	44.4	19	22.2	0.35
1-1/4	TM20	160	50.8	50.8	20	28.5	0.55
1-1/2	TM24	125	57.1	57.1	22	33.3	0.78
2	TM32	80	63.1	63.1	25	46.1	1.04

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Hydraulic All Male Tee's are available in Male BSPB threads, with a 60° internal cone on all outlets of the Male threads

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPB Male threads are to ISO 228/1  
60° internal cone to BS 5200

We also keep a Swivel Female version of this fitting + Bonded Washers in our Hydraulic range

We stock a wide range of Hydraulic Fittings to suit your requirements

