



SIZE	CODE BSP	DIMENSIONS		
		SW	A	KG EACH
1/8	UCMM02	29.1	52	0.09
1/4	UCMM04	29.1	55.5	0.11
3/8	UCMM06	34	60.5	0.15
1/2	UCMM08	37.5	66	0.16
3/4	UCMM12	44.5	72.5	0.23
1	UCMM16	53.5	84.5	0.40
1-1/4	UCMM20	64	90	0.54
1-1/2	UCMM24	71.5	99	0.72
2	UCMM32	85.5	110	1.05

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Conical Male x Male Unions are available threaded BSP.
They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method
Note 2 Temperatures indicated are those of the Internal fluid
Note 3 Piping loads, stresses And moments are not taken into account

Not the union you are looking for? see below for more options

