



| SIZE | CODE | | DIMENSIONS | | |
|---------------|--------|---------|------------|------|---------|
| | BSP | NPT | A | B | KG EACH |
| 1/4 x 1/8 | RN0402 | RN0402N | 14.5 | 10.5 | 0.01 |
| 3/8 x 1/8 | RN0602 | - | 18 | 11 | 0.02 |
| 3/8 x 1/4 | RN0604 | - | 18 | 26.5 | 0.03 |
| 1/2 x 1/8 | RN0802 | RN0604N | 21.4 | 14.5 | 0.03 |
| 1/2 x 1/4 | RN0804 | RN0804N | 21.4 | 30 | 0.04 |
| 1/2 x 3/8 | RN0806 | RN0806N | 21.4 | 30 | 0.04 |
| 3/4 x 1/4 | RN1204 | RN1204N | 27 | 31.5 | 0.05 |
| 3/4 x 3/8 | RN1206 | RN1206N | 27 | 32 | 0.05 |
| 3/4 x 1/2 | RN1208 | RN1208N | 27 | 35.5 | 0.06 |
| 1 x 1/4 | RN1604 | - | 34 | 34.5 | 0.08 |
| 1 x 3/8 | RN1606 | - | 34 | 35 | 0.09 |
| 1 x 1/2 | RN1608 | RN1608N | 34 | 38.5 | 0.09 |
| 1 x 3/4 | RN1612 | RN1612N | 34 | 39.5 | 0.10 |
| 1-1/4 x 1/2 | RN2008 | - | 42.7 | 41.5 | 0.13 |
| 1-1/4 x 3/4 | RN2012 | - | 42.7 | 42.5 | 0.14 |
| 1-1/4 x 1 | RN2016 | RN2016N | 42.7 | 45 | 0.16 |
| 1-1/2 x 1/2 | RN2408 | - | 48.6 | 41.5 | 0.16 |
| 1-1/2 x 3/4 | RN2412 | RN2412N | 48.6 | 42.5 | 0.16 |
| 1-1/2 x 1 | RN2416 | RN2416N | 48.6 | 45 | 0.18 |
| 1-1/2 x 1-1/4 | RN2420 | RN2420N | 48.6 | 47.5 | 0.19 |
| 2 x 1/2 | RN3208 | - | 60.5 | 45.5 | 0.24 |
| 2 x 3/4 | RN3212 | - | 60.5 | 46.5 | 0.25 |
| 2 x 1 | RN3216 | RN3216N | 60.5 | 49 | 0.27 |
| 2 x 1-1/4 | RN3220 | RN3220N | 60.5 | 51.5 | 0.28 |
| 2 x 1-1/2 | RN3224 | RN3224N | 60.5 | 51.5 | 0.28 |
| 2-1/2 x 1-1/2 | RN4024 | - | 78 | 54.5 | 0.45 |
| 2-1/2 x 2 | RN4032 | RN4032N | 78 | 59 | 0.48 |
| 3 x 1-1/2 | RN4824 | - | 91 | 58 | 0.63 |
| 3 x 2 | RN4832 | RN4832N | 91 | 62.5 | 0.66 |
| 3 x 2-1/2 | RN4840 | RN4840N | 91 | 64.5 | 0.66 |
| 4 x 2 | RN6432 | - | 116 | 69 | 1.07 |
| 4 x 2-1/2 | RN6440 | - | 116 | 71 | 1.06 |
| 4 x 3 | RN6448 | RN6448N | 116 | 74 | 1.12 |

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of 150lb fittings are available threaded BSPT and NPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
 NPT threads are to ANSI B2.1
 Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

| TEMPERATURE (°C) | NO-SHOCK MAXIMUM WORKING PRESSURE (Bar) |
|------------------|---|
| -20 to 40 | 20 |
| 100 | 16.5 |
| 150 | 15 |
| 200 | 14 |
| 220 | 13.5 |

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK