



PIPE SIZE	DN	CODE	A	B	C	D	BOLT	KG EACH	BOLT KIT CODE
1/2	15	FEB0.5	66.68	95.25	6.35	14.29	4XM12	0.62	BK02
3/4	20	FEB0.75	73.03	101.6	6.35	14.29	4XM12	0.98	BK02
1	25	FEB1.0	82.55	114.3	7.14	14.29	4XM12	1.07	BK02
1.25	32	FEB1.25	87.31	120.65	7.94	14.29	4XM12	1.52	BK02
1.5	40	FEB1.5	98.43	133.35	8.73	14.29	4XM12	1.79	BK02
2	50	FEB2.0	114.3	152.4	9.53	17.46	4XM16	2.31	BK04
2.5	65	FEB2.5	127	165.1	10.32	17.46	4XM16	3.03	BK04
3	80	FEB3.0	146.05	184.15	11.11	17.46	4XM16	3.60	BK04
4	100	FEB4.0	177.8	215.9	12.7	17.46	8XM16	3.83	BK05
5	125	FEB5.0	209.55	254	14.29	17.46	8XM16	4.50	BK05
6	150	FEB6.0	234.95	279.4	17.46	22.23	8XM20	5.50	BK10
8	200	FEB8.0	292.1	336.55	19.05	22.23	8XM20	6.84	BK10

This flange conforms to ASTM A182 and is available in 316/L.

Full material traceability is available and 3.1B certification can be provided upon request.

Bolt kit sizes shown in the above table are for bolting two flanges together including the thickness of a gasket. If using a wafer pattern valve, longer bolts will be required.

We also keep Slip-On and Threaded flanges to this standard



We also keep Gaskets to suit all our flanges in both EPDM and Non-Asbestos materials

