



SIZE	CODE		DIMENSIONS		
	BSP	NPT	A	B	KG EACH
1/8	SP02	SP02N	7	15.5	0.015
1/4	SP04	SP04N	8	19	0.016
3/8	SP06	SP06N	9	18	0.016
1/2	SP08	SP08N	10	18.5	0.02
3/4	SP12	SP12N	14	21	0.033
1	SP16	SP16N	17	24	0.056
1-1/4	SP20	SP20N	20	28	0.098
1-1/2	SP24	SP24N	23	28	0.115
2	SP32	SP32N	28	34	0.199
2-1/2	SP40	SP40N	36	38.5	0.352
3	SP48	SP48N	40	41.5	0.515
4	SP64	SP64N	52	51.5	0.93

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

