



SIZE	CODE		DIMENSIONS		
	BSP	NPT	B	A	KG EACH
1/8	BN02	BN02N	30mm	10.3	0.0129
1/4	BN04	BN04N	30mm	13.7	0.0265
3/8	BN06	BN06N	40mm	17.2	0.035
1/2	BN08	BN08N	60mm	21.3	0.073
3/4	BN12	BN12N	60mm	26.7	0.094
1	BN16	BN16N	60mm	33.4	0.143
1-1/4	BN20	BN20N	80mm	42.2	0.244
1-1/2	BN24	BN24N	80mm	48.3	0.28
2	BN32	BN32N	100mm	60.3	0.495
2-1/2	BN40	BN40N	100mm	76.1	0.638
3	BN48	BN48N	120mm	88.9	0.97
4	BN64	BN64N	120mm	114.3	1.43
5	BN80	BN80N	150mm	141.3	1.6
6	BN96	BN96N	150mm	168.3	3.25

We also keep extended barrel nipples in stock, weld nipples too.



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLo AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK