



PIPE SIZE	DN	CODE BSPP	A	B	C	D	E	F	G	H	J	BOLT	KG EACH	BOLT KIT CODE
1/2	15	F150SP0.5	34.9	60.3	88.9	30.2	15.9	1.6	11.1	15.9	3	4XM12	0.40	BK02
3/4	20	F150SP0.75	42.9	69.8	98.4	38.1	15.9	1.6	12.7	15.9	3	4XM12	0.70	BK03
1	25	F150SP1.0	50.8	79.4	107.9	49.2	17.5	1.6	14.3	15.9	3	4XM12	0.90	BK03
1.25	32	F150SP1.25	63.5	88.9	117.5	58.7	20.6	1.6	15.9	15.9	3	4XM12	1.20	BK03
1.5	40	F150SP1.5	73	98.4	127	65.1	22.2	1.6	17.5	15.9	3	4XM12	1.50	BK03
2	50	F150SP2.0	92.1	120.6	152.4	77.8	25.4	1.6	19	19	3	4XM16	2.30	BK04
2.5	65	F150SP2.5	104.8	139.7	177.8	90.5	28.6	1.6	22.2	19	3	4XM16	3.70	BK06
3	80	F150SP3.0	127	152.4	190.5	107.9	30.2	1.6	23.8	19	3	4XM16	4.20	BK06
4	100	F150SP4.0	157.2	190.5	228.6	134.9	33.3	1.6	23.8	19	3	8XM16	5.90	BK07

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

This flange conforms to ANSI/ASME B16.5 and is available in 316/L. The threads are to ISO 7/1, 228/1 and ANSI B2.1.

Full material traceability is available and 3.1B certification can be provided upon request.

Bolt kit sizes shown in the above table are for bolting two flanges together including the thickness of a gasket. If using a wafer pattern valve, longer bolts will be required.

We also keep Slip-On, Blind and Weld Neck flanges to this standard



We also keep Gaskets to suit all our flanges in both EPDM and Non-Asbestos materials

