



SIZE	CODE	DIMENSIONS		
	BSP	A	B	KG EACH
1/8	MB02	25.6	56	0.05
1/4	MB04	31.8	64	0.08
3/8	MB06	38.1	73	0.131
1/2	MB08	44.5	86	0.229
3/4	MB12	57.2	102	/363
1	MB16	76.2	121	/637
1-1/4	MB20	88.9	146	1.04
1-1/2	MB24	108	165	1.39
2	MB32	152.4	203	2.29

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Not the elbow you are looking for? see below for more options



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK