



PIPE SIZE	DN	CODE	A	B	C	D	E	BOLT	Kg EACH	BOLT KIT CODE
1/2	15	FES0.5	66.68	22.35	95.25	6.35	14.29	4XM12	0.34	BK02
3/4	20	FES0.75	73.03	27.69	101.6	6.35	14.29	4XM12	0.36	BK02
1	25	FES1.0	82.55	34.54	114.3	7.14	14.29	4XM12	0.5	BK02
1.25	32	FES1.25	87.31	43.18	120.7	7.94	14.29	4XM12	0.64	BK02
1.5	40	FES1.5	98.43	49.53	133.4	8.73	14.29	4XM12	1	BK02
2	50	FES2.0	114.3	61.98	152.4	9.53	17.46	4XM16	1.14	BK04
2.5	65	FES2.5	127	74.68	165.1	10.32	17.46	4XM16	1.44	BK04
3	80	FES3.0	146.1	90.68	184.2	11.11	17.46	4XM16	1.84	BK04
4	100	FES4.0	177.8	116.1	215.9	12.7	17.46	8XM16	2.53	BK05
5	125	FES5.0	209.6	143.8	254	14.29	17.46	8XM16	3	BK05
6	150	FES6.0	235	170.7	279.4	17.46	22.23	8XM20	4	BK10
8	200	FES8.0	292.1	221.5	336.6	19.05	22.23	8XM20	4.87	BK10

This flange conforms to ASTM A182 and is available in 316/L.

Full material traceability is available and 3.1B certification can be provided upon request.

Bolt kit sizes shown in the above table are for bolting two flanges together including the thickness of a gasket. If using a wafer pattern valve, longer bolts will be required.

We also keep blind and threaded flanges to this standard



Need a gasket?
We keep those too

