



SIZE	CODE BSP	DIMENSIONS		
		A	B	KG EACH
1/8	UCMF02	29.1	35.5	0.09
1/4	UCMF04	29.1	46	0.11
3/8	UCMF06	34	47.5	0.15
1/2	UCMF08	37.5	53.6	0.16
3/4	UCMF12	44.5	58.3	0.23
1	UCMF16	53.5	69	0.40
1-1/4	UCMF20	64	71.1	0.54
1-1/2	UCMF24	71.5	80	0.72
2	UCMF32	85.5	88.2	1.05

\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Conical Male x Female Unions are available threaded BSPP x BSPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1  
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method  
Note 2 Temperatures indicated are those of the Internal fluid  
Note 3 Piping loads, stresses And moments are not taken into account

Not the union you are looking for? see below for more options