



SIZE	CODE	DIMENSIONS		
	BSP	A1	A2	KG EACH
1/4x1/8	RE0402	20	20	0.036
3/8x1/4	RE0604	21	20.2	0.034
1/2x1/4	RE0804	28	27.5	0.096
1/2x3/8	RE0806	39	25.5	0.064
3/4x3/8	RE1206	26.7	25	0.069
3/4x1/2	RE1208	28.8	29	0.109
1x1/2	RE1608	33.7	31	0.133
1x3/4	RE1612	35.8	32.2	0.138
1-1/4x3/4	RE2012	39.8	36.8	0.188
1-1/4x1	RE2016	41	41	0.24
1-1/2x1	RE2416	43.5	40	0.268
1-1/2x1-1/4	RE2420	46.9	44.7	0.34
2x1	RE3216	49.5	45	0.368
2x1-1/4	RE3220	54.6	48.7	0.424
2x1-1/2	RE3224	54.6	52	0.469

NERO's range of 150Lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Not the elbow you are looking for? see below for more options

