



SIZE	PRODUCT CODE BSPT	PRODUCT CODE NPT	LENGTH OF THREAD (MIN)		W	D	KG EACH
			B	L2			
1/8	3S02T	3S02N	6.4	6.7	32	16	0.04
1/4	3S04T	3S04N	8.1	10.2	35	19	0.05
3/8	3S06T	3S06N	9.1	10.4	38	22	0.07
1/2	3S08T	3S08N	10.9	13.6	48	28	0.14
3/4	3S12T	3S12N	12.7	13.9	51	35	0.23
1	3S16T	3S16N	14.7	17.3	60	44	0.45
1-1/4	3S20T	3S20N	17.0	18	67	57	0.73
1-1/2	3S24T	3S24N	17.8	18.4	79	64	1.18
2	3S32T	3S32N	19.0	19.2	86	76	1.40
2-1/2	3S40T	3S40N	23.6	28.9	92	92	2.29
3	3S48T	3S48N	25.9	30.5	108	108	3.38

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Full Couplings are available in BSPT, BSPP, NPT and Socket Weld configurations - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1
NPT threads are to ANSI B2.1

Larger sizes are available upon request

We also keep Full Couplings in Socket Weld 3000lb 316/L



Couplings can also be supplied as part of our low pressure 150lb range

