



SIZE	DIMENSIONS			
	BSP	SW	A	KG EACH
1/8	UFMM02	29.1	42	0.089
1/4	UFMM04	29.1	44.5	0.109
3/8	UFMM06	34	48.5	0.152
1/2	UFMM08	37.5	68	0.164
3/4	UFMM12	44.5	75	0.23
1	UFMM16	53.5	87.5	0.401
1-1/4	UFMM20	64	93	0.544
1-1/2	UFMM24	71.5	103	0.724
2	UFMM32	85.5	115	1.055

NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Not the union you are looking for? see below for more options



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLo AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK