



PIPE SIZE	DN	CODE 316	CODE 304	A	B	C	D	E	F	G	BOLT	KG EACH	BOLT KIT CODE
1/2	15	F630.5	F630.5-304	40	55	80	22	12	2	11	4XM10	0.41	BK01
3/4	20	F630.75	F630.75-304	50	65	90	27.5	14	2	11	4XM10	0.60	BK01
1	25	F631.0	F631.0-304	60	75	100	34.5	14	2	11	4XM10	0.73	BK01
1.25	32	F631.25	F631.25-304	70	90	120	43.5	16	2	14	4XM12	1.17	BK03
1.5	40	F631.5	F631.5-304	80	100	130	49.5	16	3	14	4XM12	1.36	BK03
2	50	F632.0	F632.0-304	90	110	140	61.5	16	3	14	4XM12	1.50	BK03
2.5	65	F632.5	F632.5-304	110	130	160	74.7	16	3	14	4XM12	1.87	BK03
3	80	F633.0	F633.0-304	128	150	190	90.5	18	3	18	4XM16	2.98	BK04
4	100	F634.0	F634.0-304	148	170	210	116	20	3	18	4XM16	3.29	BK04
5	125	F635.0	F635.0-304	178	200	240	143.8	20	3	18	8XM16	4.36	BK07
6	150	F636.0	F636.0-304	202	225	265	170.5	22	3	18	8XM16	4.80	BK07
8	200	F638.0	F638.0-304	258	280	320	221.5	22	3	18	8XM16	6.30	BK07

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

This flange conforms to EN 1092-1 and is available in both 316/L and 304/L.

Full material traceability is available and 3.1B certification can be provided upon request.

Bolt kit sizes shown in the above table are for bolting two flanges together including the thickness of a gasket. If using a wafer pattern valve, longer bolts will be required.

We also keep Gaskets to suit all our flanges in both EPDM and Non-Asbestos materials



We also keep Blind and Threaded flanges to this standard

