



SIZE BSPP (G)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	HEX	KG EACH
1/8	FFA02	350	23.1	4.1	3.5	14.3	0.03
1/4	FFA04	350	25.6	4.2	4.7	18.1	0.06
3/8	FFA06	350	31.2	4.6	8.1	22.2	0.09
1/2	FFA08	315	29.7	6.8	11.1	25.6	0.15
3/4	FFA12	250	36.3	8.7	16.6	31.7	0.21
1	FFA16	200	40.8	10.1	22.2	28.1	0.35
1-1/4	FFA20	160	39.6	10.5	28.5	47.2	0.55
1-1/2	FFA24	125	53.1	12.2	33.3	56.4	0.78
2	FFA32	80	57.1	15.1	46.1	69.8	1.04

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Swivel Adaptors are available in BSPP x BSPP threads, with a 60° internal cone on the Female Swivel ends

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate of Conformity - upon request

BSPP Female thread are to ISO 228/1  
60° internal cone to BS 5200

We stock a wide range of Hydraulic Fittings to suit your requirements



We also keep a BSPP Female Swivel x Male BSPT in our Hydraulic range + Bonded Washers in our Hydraulic range



5 STAR ★★★★★  
CUSTOMER SERVICE



SAME DAY DISPATCH -  
ORDERS PLACED BEFORE 4:30PM



WEALTH OF  
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST  
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: [INFO@NERO.CO.UK](mailto:info@nero.co.uk)

UNIT 2, UNION RD, ANGLO AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

[WWW.NERO.CO.UK](http://WWW.NERO.CO.UK)