


H-Thrd's Minimum 4 Full Thrd's Engagement Class 2A / 2B Fit ANSI B1.1





						DIMENSION	S				
SIZE	PRODUCT CODE	PIPE END A (MIN)	WALL C (MIN)	WATER WAY BORE D*	MALE FLANGE F (MIN)	NUT G (MIN)	THREADS PER 25.4MM H	BEARING J (MIN)	LENGTH ASSEM. NOM. L	CLEAR ASSEM. NOM. N	KG EACH
1/2	6UC08N	31.0	4.78	17.86 / 11.02	4.06	4.06	11	1.68	56.9	66.0	0.55
3/4	6UC12N	37.8	5.56	23.01 / 14.78	4.57	4.45	11	1.85	62.0	78.7	0.92
1	6UC16N	46.2	6.35	28.98 / 19.94	5.33	5.21	10	2.13	71.1	94.0	1.28

<sup>\*</sup> Upper and Lower values for each size are the respective maximum and minimum dimensions

## \*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Cone Seat Unions are available in NPT and Socket Weld configurations - ASME B16.11-2016

Pressure rating up to 400 BAR (6000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

NPT threads are to ANSI B2.1

Larger sizes are available upon request

Cone Seat Unions can also be supplied as part of our low pressure 150lb range in Female, Male/Female, Male/Male and Butt Weld ends



















