





TO WORK OUT THE INSIDE DIAMETER OF PIPE - Multiply the Wall Thickness by 2 - Then deduct this number off the OD of the Pipe

| | | CODE | | | | | DIMENSIONS | | | MAXIMUM WORKING PRESSURE (PSI) | | KG / MTR | |
|-----------|-----|-------------------|-------------------|-------------------|-------------------|--------|------------|-----------|-------|-----------------------------------|-------|----------|--|
| PIPE SIZE | DN | SCHEDULE 10 316/L | SCHEDULE 10 304/L | SCHEDULE 40 316/L | SCHEDULE 40 304/L | A (OD) | B (SCH10) | B (SCH40) | SCH10 | SCH40 | SCH10 | SCH40 | |
| 1/8 | 6 | - | - | 0.125\$40316W | - | 10.29 | - | 1.73 | - | 6288 | - | 0.37 | |
| 1/4 | 8 | - | - | 0.25\$40316W | - | 13.72 | - | 2.24 | - | 6106 | - | 0.64 | |
| 3/8 | 10 | - | - | 0.375\$40316W | - | 17.15 | - | 2.31 | - | 5351 | - | 0.87 | |
| 1/2 | 15 | 0.5\$10316W | 0.5\$10304W | 0.5\$40316W | 0.5\$40304W | 21.34 | 2.11 | 2.77 | 3785 | 5133 | 1.02 | 1.29 | |
| 3/4 | 20 | 0.75\$10316W | 0.75S10304W | 0.75\$40316W | 0.75\$40304W | 26.67 | 2.11 | 2.87 | 2973 | 3466 | 1.3 | 1.71 | |
| 1 | 25 | 1.0S10316W | 1.0S10304W | 1.0S40316W | 1.0S40304W | 33.40 | 2.77 | 3.38 | 2610 | 3234 | 2.13 | 2.54 | |
| 1-1/4 | 32 | 1.25\$10316W | 1.25\$10304W | 1.25\$40316W | 1.25\$40304W | 42.16 | 2.77 | 3.56 | 2030 | 2654 | 2.73 | 3.44 | |
| 1-1/2 | 40 | 1.5\$10316W | 1.5S10304W | 1.5\$40316W | 1.5S40304W | 48.26 | 2.77 | 3.68 | 1769 | 2378 | 3.16 | 4.11 | |
| 2 | 50 | 2.0S10316W | 2.0S10304W | 2.0\$40316W | 2.0\$40304W | 60.33 | 2.77 | 3.91 | 1392 | 2001 | 3.99 | 5.52 | |
| 2-1/2 | 65 | 2.5\$10316W | 2.5\$10304W | 2.5\$40316W | 2.5\$40304W | 73.03 | 3.05 | 5.16 | 1262 | 2204 | 5.34 | 8.77 | |
| 3 | 80 | 3.0\$10316W | 3.0S10304W | 3.0\$40316W | 3.0S40304W | 88.90 | 3.05 | 5.49 | 1030 | 1900 | 6.56 | 11.47 | |
| 4 | 100 | 4.0S10316W | 4.0S10304W | 4.0\$40316W | 4.0S40304W | 114.30 | 3.05 | 6.02 | 798 | 1610 | 8.5 | 16.32 | |
| 5 | 125 | 5.0\$10316W | 5.0S10304W | 5.0\$40316W | 5.0S40304W | 141.30 | 3.40 | 6.55 | 711 | 1407 | 11.74 | 22.1 | |
| 6 | 150 | 6.0\$10316W | 6.0S10304W | 6.0\$40316W | 6.0S40304W | 168.28 | 3.40 | 7.11 | 595 | 1276 | 14.04 | 28.69 | |
| 8 | 200 | 8.0\$10316W | 8.0S10304W | 8.0\$40316W | 8.0S40304W | 219.08 | 3.76 | 8.18 | 508 | 1131 | 20.27 | 43.2 | |
| 10 | 250 | 10.0S10316W | 10.0S10304W | 10.0S40316W | 10.0\$40304W | 273.05 | 4.19 | 9.27 | 450 | 1015 | 28.2 | 61.22 | |
| 12 | 300 | 12.0S10316W | 12.0S10304W | - | 12.0S40304W | 323.85 | 4.57 | 9.53 | 421 | 885 | 36.54 | 80.9 | |

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Welded pipe is to ASTM A312/ANSI B36.19 and is available in 316/304/L material and Schedule 10 and 40 thickness.

We keep all sizes in full random lengths (6 metres) and sell by the metre, this enables us to supply lengths as short as 1 metre long.

We can also offer and accurate cutting service on any of our pipe to a tolerance of +/- 1mm.





S STAR *****

Q.

SAME DAY DISPATCH -ORDERS PLACED BEFORE 4:30PM





CALL: +44 (D)121 665 3900 EMAIL: INFD@NERD.CD.UK

IIT 2, UNION RD, ANGLO AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS 869 38

WWW.NERO.CO.UK