



GDPRESS fittings offer reliable and consistent performance, combined with an easy installation process using common M-contour design and tooling compatibility.

Each end has a toroidal seat, holding a rubber LBP (Leak before press) O-ring gasket. The fittings are installed with blue sleeves, which easily peel off after the pressing process.

All fittings are made from 316L (1.4404)
WRAS approved

Optional Fluoropolymer (FPM) O-rings are also available which offer higher heat and chemical resistance



SIZE	PART No	D	L	Z	KG EACH
15	PFC15	15	48	8	0.03
18	PFC18	18	48	8	0.04
22	PFC22	22	50	8	0.05
28	PFC28	28	54	8	0.07
35	PFC35	35	62	10	0.10
42	PFC42	42	71	11	0.14
54	PFC54	54	83	13	0.19
76.1	PFC76.1	76.1	141	35	0.59
88.9	PFC88.9	88.9	162	42	0.77
108	PFC108	108.0	194	44	1.19

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

Application	Operating temperature	Maximum operating pressure	Seal
Hot and cold potable water	0 to 100°C	16 BAR	EPDM
Heating water	0 to 100°C	16 BAR	EPDM
Cooling water without antifreeze agent	0 to 100°C	16 BAR	EPDM
Cooling water with antifreeze agent	-30 to +120°C	16 BAR	EPDM
Service/Treated water	0 to 100°C	16 BAR	EPDM
Rainwater/Grey and black water with a pH value of >6.0	0 to 100°C	16 BAR	EPDM
Extinguishing water	0 to 70°C	16 BAR	EPDM
Extinguishing water (wet/dry, dry)	0 to 70°C	16 BAR	FPM
Sprinklers	0 to 70°C	16 BAR	EPDM
Oils, Fuels and Chemicals	Please contact	Please contact	FPM



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK