





SIZE	PRODUCT CODE	В	С		D		G (MIN)	J (MIN)	KG EACH
			AVG	MIN	D	A	G (IVIIIV)	J (IVIIIV)	KG EACH
1/4	3EA04SW	14.2	3.78	3.30	9.3	8.0	3.02	9.5	0.08
3/8	3EA06SW	17.6	4.01	3.50	12.6	8.0	3.20	9.5	0.11
1/2	3EA08SW	21.8	4.67	4.09	15.8	11.0	3.73	9.5	0.20
3/4	3EA12SW	27.2	4.90	4.27	21.0	13.0	3.91	12.5	0.29
1	3EA16SW	33.9	5.69	4.98	26.7	14.0	4.55	12.5	0.43
1-1/4	3EA20SW	42.7	6.07	5.28	35.1	17.5	4.85	12.5	0.69
1-1/2	3EA24SW	48.8	6.35	5.54	40.9	20.5	5.08	12.5	0.79
2	3EA32SW	61.2	6.93	6.04	52.5	25.5	5.54	16.0	1.35

<sup>\*\*</sup> DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of 45 Degree Elbows are available in BSPT, NPT and Socket Weld configurations

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799

Larger sizes are available upon request

## Elbows can also be supplied in 90 or 45 Degree as part of our low pressure 150lb





We also keep 45 Degree Elbows in BSPT and NPT thread types in 3000lb 316/L









