



SIZE	PRODUCT CODE	DIMENSIONS								KG EACH
		H	A	J	G1 (MIN)	G2 (MIN)	B (MIN)	L2 (MIN)	L	
1/4	3SE04N	25	22	32	3.30	3.22	8.1	10.2	11.0	0.11
3/8	3SE06N	32	25	38	3.51	3.50	9.1	10.4	13.0	0.24
1/2	3SE08N	38	28	41	4.09	4.16	10.9	13.6	14.0	0.34
3/4	3SE12N	44	35	48	4.32	4.88	12.7	13.9	16.0	0.55
1	3SE16N	51	44	57	4.98	5.56	14.7	17.3	19.0	1.02
1-1/4	3SE20N	62	51	66	5.28	5.56	17.0	18.0	21.0	1.24
1-1/2	3SE24N	70	54	71	5.56	6.25	17.8	18.4	21.0	2.01
2	3SE32N	84	64	84	7.14	7.64	19.0	19.0	22.0	2.91

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Street Elbows are available in NPT thread type - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

NPT threads are to ANSI B2.1

Larger sizes are available upon request

Street Elbows can also be supplied in 90° and 45° as part of our low pressure 150lb range



We also keep 90° Elbows with a female thread type both ends and in Socket Weld in 3000lb 316/L



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLA AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK