





SIZE	PRODUCT CODE	PRODUCT CODE	LENGTH OF THREAD (MIN)		В	D	G (MIN)	KG EACH
	BSPT	NPT	В	L2	Р	U	G (IVIIIV)	NG EACH
1/8	3RC02T	3RC02N	6.4	6.7	19	16	4.8	0.03
1/4	3RC04T	3RC04N	8.1	10.2	25	19	4.8	0.04
3/8	3RC06T	3RC06N	9.1	10.4	25	22	4.8	0.05
1/2	3RC08T	3RC08N	10.9	13.6	32	28	6.4	0.11
3/4	3RC12T	3RC12N	12.7	13.9	37	35	6.4	0.18
1	3RC16T	3RC16N	14.7	17.3	41	44	9.7	0.33
1-1/4	3RC20T	3RC20N	17.0	18.0	44	57	9.7	0.62
1-1/2	3RC24T	3RC24N	17.8	18.4	44	64	11.2	0.72
2	3RC32T	3RC32N	19.0	19.2	48	76	12.7	1.09

<sup>\*\*</sup> DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\*

NERO's range of Round Caps are available in BSPT, NPT and Socket Weld configurations - ASME B16.11-2016

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

BSPT threads are to ISO 7.1 NPT threads are to ANSI B2.1

Larger sizes are available upon request

## Caps can also be supplied as Hex or Round as part of our low pressure 150lb range





## We also keep Round Caps in Socket Weld 3000lb 316/L









