

SIZE	PRODUCT CODE	B	C		D	E	J (MIN)	KG EACH
			AVG	MIN				
1/8	3S02SW	10.8	3.18	3.18	6.9	6.5	9.5	0.05
1/4	3S04SW	14.2	3.78	3.30	9.3	6.5	9.5	0.05
3/8	3S06SW	17.6	4.01	3.50	12.6	6.5	9.5	0.07
1/2	3S08SW	21.8	4.67	4.09	15.8	9.5	9.5	0.13
3/4	3S12SW	27.2	4.90	4.27	21.0	9.5	12.5	0.19
1	3S16SW	33.9	5.69	4.98	26.7	12.5	12.5	0.33
1-1/4	3S20SW	42.7	6.07	5.28	35.1	12.5	12.5	0.41
1-1/2	3S24SW	48.8	6.35	5.54	40.9	12.5	12.5	0.59
2	3S32SW	61.2	6.93	6.04	52.5	19.0	16.0	0.86

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Full Couplings are available in BSPT, BSPP, NPT and Socket Weld configurations


Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799

Larger sizes are available upon request

Couplings can also be supplied as part of our low pressure 150lb range



We also keep Full Couplings in BSPT, BSPP and NPT thread types in 3000lb 316/L

