



SIZE	CODE		DIMENSIONS		
	BSP	SW	A	B	KG EACH
1/8	C02	C02SW	16.4	17	0.05
1/4	C04	C04SW	20	18.8	0.08
3/8	C06	C06SW	23.5	23	0.13
1/2	C08	C08SW	27.5	27	0.15
3/4	C12	C12SW	32.7	31.5	0.21
1	C16	C16SW	40.3	36.5	0.34
1-1/4	C20	C20SW	49	42.5	0.47
1-1/2	C24	C24SW	55.5	47.5	0.64
2	C32	C32SW	67.8	56.5	0.93
2-1/2	C40	C40SW	86.5	67	2.59
3	C48	C48SW	101.7	77.5	3.83
4	C64	C64SW	124	93.5	5.5

We also keep extended barrel nipples in stock, weld nipples too.



NERO's range of 150lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK