



SIZE	CODE BSP	DIMENSIONS		
		A1	A2	KG EACH
1/4 x 1/8	RE0402	20	20	0.04
3/8 x 1/4	RE0604	21	20.2	0.03
1/2 x 1/4	RE0804	28	27.5	0.10
1/2 x 3/8	RE0806	39	25.5	0.06
3/4 x 3/8	RE1206	26.7	25	0.07
3/4 x 1/2	RE1208	28.8	29	0.11
1 x 1/2	RE1608	33.7	31	0.13
1 x 3/4	RE1612	35.8	32.2	0.14
1-1/4 x 3/4	RE2012	39.8	36.8	0.19
1-1/4 x 1	RE2016	41	41	0.24
1-1/2 x 1	RE2416	43.5	40	0.27
1-1/2 x 1-1/4	RE2420	46.9	44.7	0.34
2 x 1	RE3216	49.5	45	0.37
2 x 1-1/4	RE3220	54.6	48.7	0.42
2 x 1-1/2	RE3224	54.6	52	0.47

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Reducing Elbows are available threaded BSP. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

Not the elbow you are looking for? see below for more options

