



SIZE	CODE		DIMENSIONS		
	BSP	NPT	B	A	KG EACH
1/8	BN02	BN02N	30mm	10.3	0.01
1/4	BN04	BN04N	30mm	13.7	0.03
3/8	BN06	BN06N	40mm	17.2	0.04
1/2	BN08	BN08N	60mm	21.3	0.07
3/4	BN12	BN12N	60mm	26.7	0.09
1	BN16	BN16N	60mm	33.4	0.14
1-1/4	BN20	BN20N	80mm	42.2	0.24
1-1/2	BN24	BN24N	80mm	48.3	0.28
2	BN32	BN32N	100mm	60.3	0.50
2-1/2	BN40	BN40N	100mm	76.1	0.64
3	BN48	BN48N	120mm	88.9	0.97
4	BN64	BN64N	120mm	114.3	1.43
5	BN80	BN80N	150mm	141.3	1.60
6	BN96	BN96N	150mm	168.3	3.25

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Barrel Nipples are available threaded BSPT and NPT

BSPT threads are to ISO 7-1

NPT threads are to ANSI B2.1

Made from 316/L stainless steel pipe

Maximum Working Pressure of 50 BAR

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	50
100	50
150	35
200	25
220	20

Note 1 Pressure for intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.



5 STAR ★★★★★
CUSTOMER SERVICE



SAME DAY DISPATCH -
ORDERS PLACED BEFORE 4:30PM



WEALTH OF
INDUSTRY KNOWLEDGE



ONE OF THE LARGEST
STOCKISTS IN THE UK

CALL: +44 (0)121 665 3900 EMAIL: INFO@NERO.CO.UK

UNIT 2, UNION RD, ANGLA AFRICAN INDUSTRIAL ESTATE, OLDBURY, WEST MIDLANDS B69 3EX

WWW.NERO.CO.UK