



SIZE	CODE	DIMENSIONS				KG EACH
	BSP	A	B	C	D	
1/4 X 1/8	RT0402	13.5	17.2	17	15.3	0.0358
3/8 X 1/4	RT0604	17	19.1	21.4	20.2	0.059
1/2 X 1/4	RT0804	17.5	19	25.4	21.5	0.064
1/2 X 3/8	RT0806	21.4	20.5	25.4	21.9	0.069
3/4 X 3/8	RT1206	21.4	21.5	30.9	24.6	0.086
3/4 X 1/2	RT1208	25.4	24	30.9	27.7	0.1
1 X 1/2	RT1608	25.4	26	37.9	31.1	0.142
1 X 3/4	RT1612	30.9	29	37.9	32.1	0.159
1-1/4 X 1/2	RT2008	30.9	31	47.4	36.5	0.231
1-1/4 X 3/4	RT2012	30.9	34.5	47.4	39	0.263
1-1/4 X 1	RT2016	37.9	31.5	53.2	39.4	0.264
1-1/2 X 3/4	RT2412	30	31.5	53.2	39.4	0.261
1-1/2 X 1	RT2416	37.9	35	53.2	41.9	0.296
1-1/2 X 1-1/4	RT2420	47.4	39.5	53.2	44.4	0.346
2 X 1/2	RT3208	25.4	35.5	65.7	45.3	0.383
2 X 3/4	RT3212	30.9	35.5	65.7	45.3	0.397
2 X 1	RT3216	37.9	39	65.7	47.8	0.437
2 X 1-1/4	RT3220	47.4	43.5	65.7	50.3	0.497
2 X 1-1/2	RT3224	53.2	46.5	65.7	50.3	0.52

NERO's range of 150Lb fittings are available threaded BSP and NPT, or with Socket weld end connections. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1

NPT threads are to ANSI B2.1

Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK