


S.NO.	COMPONENT	QTY	MATERIAL
1	HANDLE SLEEVE	1	PVC
2	HANDLE	1	304
3	GLAND NUT	1	304/316
4	STEM NUT	1	304
5	STEM WASHER	1	304
6	STEM PACKING	1	PTFE
7	THRUST WASHER	1	PTFE
8	END CAP	2	CF8/CF8M
9	BOLT	4(6)	304
10	NUT	4(6)	304
11	SPRING WASHER	4(6)	304
12	BODY	1	CF8/CF8M
13	BALL SEAT	2	RPTFE
14	BALL	1	CF8/CF8M
15	STEM	1	304/316
16	LOCKING DEVICE	1	304

- Pressure rated at 1000 PSI (WOG) - 1/4" --> 2"
- Pressure rated at 800 PSI (WOG) - 2-1/2" --> 4"
- Sizes available from 1/4" up to 4"
- 3-Piece Full Bore / Port
- Threaded Ends: BSPP (ISO 228-1) NPT (ANSI B2.1)
- Investment casting Body & Cap
- Internal entry blow-out proof stem
- Inspection Testing: API 598, / EN12266
- 1/4 turn lockable handle
- PED97/23/PE (CE0035) Approved



SIZE	PRODUCT CODE		D	L	H	W	CV FACTOR	KG EACH
	BSPP	NPT						
1/4	FBVX04	FBVX04N	11	50	48	103	6	0.41
3/8	FBVX06	FBVX06N	12	50	48	103	7	0.44
1/2	FBVX08	FBVX08N	15	60	52	103	10	0.65
3/4	FBVX12	FBVX12N	20	70	61	123	25	0.80
1	FBVX16	FBVX16N	25	80	65	123	35	1.20
1-1/4	FBVX20	FBVX20N	32	93	79	153	46	2.05
1-1/2	FBVX24	FBVX24N	38	100	83	153	80	2.80
2	FBVX32	FBVX32N	50	125	97	185	110	4.29
2-1/2	FBVX40	FBVX40N	64	158	135	243	310	8.40
3	FBVX48	FBVX48N	76	179	144	243	360	14.15
4	FBVX64	FBVX64N	94	223	172	315	820	26.50

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

