


SIZE	SCHEDULE 10									SCHEDULE 40								
	PRODUCT CODE		DIMENSIONS						KG	PRODUCT CODE		DIMENSIONS						KG
	316/L	304/L	A OD	B OD	C	D	E	F			316/L	304/L	A OD	B OD	C	D	E	
3/4 X 1/2	BRT1208/1	BRT1208/1-304	26.6	21.3	2.11	2.11	29	29	0.12	BRT1208/4	BRT1208/4-304	26.6	21.3	2.77	2.87	29	29	0.18
1 X 1/2	BRT1608/1	BRT1608/1-304	33.4	21.3	2.11	2.77	38	38	0.20	BRT1608/4	BRT1608/4-304	33.4	21.3	2.77	3.38	38	38	0.23
1 X 3/4	BRT1612/1	BRT1612/1-304	33.4	26.6	2.11	2.77	38	38	0.21	BRT1612/4	BRT1612/4-304	33.4	26.6	2.87	3.38	38	38	0.24
1-1/4 X 1	BRT2016/1	BRT2016/1-304	42.1	33.4	2.77	2.77	48	48	0.34	BRT2016/4	BRT2016/4-304	42.1	33.4	3.38	3.56	48	48	0.44
1-1/2 X 1/2	BRT2408/1	BRT2408/1-304	48.3	21.3	2.11	2.77	57	57	0.39	-	-	-	-	-	-	-	-	-
1-1/2 X 3/4	BRT2412/1	BRT2412/1-304	48.3	26.6	2.11	2.77	57	57	0.43	-	BRT2412/4-304	48.3	26.6	2.87	3.68	57	57	0.55
1-1/2 X 1	BRT2416/1	BRT2416/1-304	48.3	33.4	2.77	2.77	57	57	0.46	BRT2416/4	BRT2416/4-304	48.3	33.4	3.38	3.68	57	57	0.60
1-1/2 X 1-1/2	BRT2420/1	BRT2420/1-304	48.3	42.1	2.77	2.77	57	57	0.48	BRT2420/4	BRT2420/4-304	48.3	42.1	3.56	3.68	57	57	0.63
2 X 1/2	BRT3208/1	BRT3208/1-304	60.3	21.3	2.11	2.77	44	64	0.56	-	-	-	-	-	-	-	-	-
2 X 3/4	BRT3212/1	BRT3212/1-304	60.3	26.6	2.11	2.77	44	64	0.64	-	-	-	-	-	-	-	-	-
2 X 1	BRT3216/1	BRT3216/1-304	60.3	33.4	2.77	2.77	51	64	0.73	BRT3216/4	BRT3216/4-304	60.3	33.4	3.38	3.91	51	64	1.14
2 X 1-1/4	BRT3220/1	BRT3220/1-304	60.3	42.1	2.77	2.77	60	64	0.75	BRT3220/4	BRT3220/4-304	60.3	42.1	3.56	3.91	60	64	1.18
2 X 1-1/2	BRT3224/1	BRT3224/1-304	60.3	48.3	2.77	2.77	60	64	0.77	BRT3224/4	BRT3224/4-304	60.3	48.3	3.68	3.91	60	64	1.23
2-1/2 X 1	BRT4016/1	BRT4016/1-304	73	33.4	2.77	3.05	57	76	1.18	BRT4016/4	BRT4016/4-304	73	33.4	3.38	5.16	57	76	1.67
2-1/2 X 1-1/2	BRT4020/1	BRT4020/1-304	73	42.1	2.77	3.05	67	76	1.18	BRT4020/4	BRT4020/4-304	73	42.1	3.56	5.16	67	76	1.88
2-1/2 X 1-1/2	BRT4024/1	BRT4024/1-304	73	48.3	2.77	3.05	67	76	1.18	BRT4024/4	BRT4024/4-304	73	48.3	3.68	5.16	67	76	2.08
2-1/2 X 2	BRT4032/1	BRT4032/1-304	73	60.3	2.77	3.05	70	76	1.21	BRT4032/4	BRT4032/4-304	73	60.3	3.91	5.16	70	76	2.12
3 X 1	BRT4816/1	BRT4816/1-304	88.9	33.4	2.77	3.05	73	86	1.39	BRT4816/4	BRT4816/4-304	88.9	33.4	3.38	5.49	73	86	2.44
3 X 1-1/4	BRT4820/1	BRT4820/1-304	88.9	42.3	2.77	3.05	73	86	1.60	BRT4820/4	BRT4820/4-304	88.9	42.3	3.56	5.49	73	86	2.71
3 X 1-1/2	BRT4824/1	BRT4824/1-304	88.9	48.3	2.77	3.05	73	86	1.60	BRT4824/4	BRT4824/4-304	88.9	48.3	3.68	5.49	73	86	2.98
3 X 2	BRT4832/1	BRT4832/1-304	88.9	60.3	2.77	3.05	76	86	1.63	BRT4832/4	BRT4832/4-304	88.9	60.3	3.91	5.49	76	86	3.01
3 X 2-1/2	BRT4840/1	BRT4840/1-304	88.9	73	3.05	3.05	83	86	1.69	BRT4840/4	BRT4840/4-304	88.9	73	5.16	5.49	83	86	3.15
4 X 1-1/2	BRT6424/1	BRT6424/1-304	114.3	48.3	2.77	3.05	86	105	2.35	-	-	-	-	-	-	-	-	-
4 X 2	BRT6432/1	BRT6432/1-304	114.3	60.3	2.77	3.05	89	105	2.53	BRT6432/4	BRT6432/4-304	114.3	60.3	3.91	6.02	89	105	5.08
4 X 2-1/2	BRT6440/1	BRT6440/1-304	114.3	73	3.05	3.05	95	105	2.59	BRT6440/4	BRT6440/4-304	114.3	73	5.16	6.02	95	105	5.22
4 X 3	BRT6448/1	BRT6448/1-304	114.3	88.9	3.05	3.05	98	105	2.61	BRT6448/4	BRT6448/4-304	114.3	88.9	5.49	6.02	98	105	5.27
5 X 3	BRT8048/1	BRT8048/1-304	141.3	88.9	3.05	3.4	111	124	4.17	BRT8048/4	BRT8048/4-304	141.3	88.9	5.49	6.55	111	124	8.13
5 X 4	BRT8064/1	BRT8064/1-304	141.3	114.3	3.05	3.4	117	124	4.24	BRT8064/4	BRT8064/4-304	141.3	114.3	6.02	6.55	117	124	8.36
6 X 3	BRT9648/1	BRT9648/1-304	168.3	88.9	3.05	3.4	124	143	5.75	BRT9648/4	BRT9648/4-304	168.3	88.9	5.49	7.11	124	143	11.92
6 X 4	BRT9664/1	BRT9664/1-304	168.3	114.3	3.05	3.4	130	143	5.85	BRT9664/4	BRT9664/4-304	168.3	114.3	6.02	7.11	130	143	12.10
6 X 5	BRT9680/1	BRT9680/1-304	168.3	141.3	3.4	3.4	137	143	5.92	BRT9680/4	BRT9680/4-304	168.3	141.3	6.55	7.11	137	143	12.34
8 X 4	BRT12864/1	BRT12864/1-304	219.1	114.3	3.05	3.76	156	178	13.45	-	-	-	-	-	-	-	-	-
8 X 5	BRT12880/1	BRT12880/1-304	219.1	141.3	3.4	3.76	162	178	13.77	-	-	-	-	-	-	-	-	-
8 X 6	BRT12896/1	BRT12896/1-304	219.1	168.3	3.4	3.76	168	178	14.08	-	-	-	-	-	-	-	-	-
10 X 6	BRT16096/1	BRT16096/1-304	273.05	168.3	3.4	4.19	194	216	26.30	-	-	-	-	-	-	-	-	-
10 X 8	BRT160128/1	BRT160128/1-304	273.05	219.1	3.76	4.19	194	216	26.30	-	-	-	-	-	-	-	-	-
12 X 6	-	BRT19296/1-304	323.9	168.3	3.4	4.57	219	254	34.01	-	-	-	-	-	-	-	-	-
12 X 8	-	BRT192128/1-304	323.9	219.1	3.76	4.57	229	254	34.80	-	-	-	-	-	-	-	-	-
12 X 10	-	BRT192160/1-304	323.9	273.05	4.19	4.57	241	254	35.59	-	-	-	-	-	-	-	-	-

Plain bevel



Wall thickness (t)
x* mm to 22 mm

Less than x* = Cut square or slightly chamfer, at manufacturer's option.

NERO's range of Butt Weld Reducing Tee's are made to ANSI B16.9. They are available in schedule 10-40 thickness and 316/L or 304/L material grades.

This item is of Far Eastern origin and 3.1b material certificates are available upon request.



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK