



SIZE	CODE			DIMENSIONS		
	BSP	SW	NPT	A	B	KG EACH
1/8	C02	C02SW	C02N	16.4	17	0.05
1/4	C04	C04SW	C04N	20	18.8	0.08
3/8	C06	C06SW	C06N	23.5	23	0.13
1/2	C08	C08SW	C08N	27.5	27	0.15
3/4	C12	C12SW	C12N	32.7	31.5	0.21
1	C16	C16SW	C16N	40.3	36.5	0.34
1-1/4	C20	C20SW	C20N	49	42.5	0.47
1-1/2	C24	C24SW	C24N	55.5	47.5	0.64
2	C32	C32SW	C32N	67.8	56.5	0.93
2-1/2	C40	C40SW	-	86.5	67	2.59
3	C48	C48SW	-	101.7	77.5	3.83
4	C64	C64SW	-	124	93.5	5.50

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Crosses are available threaded BSPP, Socket Weld & NPT. They are made from high quality investment castings to Manufactured generally to ISO 4144

BSP threads are to ISO 7-1
NPT threads are to ANSI B2.1
Made from 316 (CF8M) stainless steel

TABLE 1: PRESSURE-TEMPERATURE RATING	
TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method
Note 2 Temperatures indicated are those of the Internal fluid
Note 3 Piping loads, stresses And moments are not taken into account

We also keep extended barrel nipples in stock, weld nipples too.