



SIZE	CODE	DIMENSIONS			KG EACH
		A	B	C	
1/8	EUCMF02	58	29.1	16.4	0.10
1/4	EUCMF04	60	29.1	20	0.11
3/8	EUCMF06	61	34	23.5	0.14
1/2	EUCMF08	64	37.5	28	0.17
3/4	EUCMF12	66.5	44.5	32.5	0.29
1	EUCMF16	81.5	53.5	42	0.47
1-1/4	EUCMF20	87.5	64	50	0.51
1-1/2	EUCMF24	101	71.5	57	0.82
2	EUCMF32	117.5	85.5	70.5	1.29

** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL **

NERO's range of Male x Female Conical Union Elbows are available threaded BSPP x BSPT. They are made from high quality investment castings to ISO4144 or above.

BSP threads are to ISO 228-1 and 7-1
Made from 316 (CF8M) stainless steel

Not the elbow you are looking for? see below for more options



TABLE 1: PRESSURE-TEMPERATURE RATING

TEMPERATURE (°C)	NO-SHOCK MAXIMUM WORKING PRESSURE (Bar)
-20 to 40	20
100	16.5
150	15
200	14
220	13.5

Note 1 Pressure for Intermediate temperatures may be determined by the interpolation method

Note 2 Temperatures indicated are those of the Internal fluid

Note 3 Piping loads, stresses And moments are not taken into account

