



| SIZE | PRODUCT CODE | B | C | | D | F | J (MIN) | KG EACH |
|-------|--------------|------|------|------|------|------|---------|---------|
| | | | AVG | MIN | | | | |
| 1/8 | 3HS02SW | 10.8 | 3.18 | 3.18 | 6.9 | 16.0 | 9.5 | 0.04 |
| 1/4 | 3HS04SW | 14.2 | 3.78 | 3.30 | 9.3 | 16.0 | 9.5 | 0.05 |
| 3/8 | 3HS06SW | 17.6 | 4.01 | 3.50 | 12.6 | 17.5 | 9.5 | 0.07 |
| 1/2 | 3HS08SW | 21.8 | 4.67 | 4.09 | 15.8 | 22.5 | 9.5 | 0.15 |
| 3/4 | 3HS12SW | 27.2 | 4.90 | 4.27 | 21 | 24.0 | 12.5 | 0.21 |
| 1 | 3HS16SW | 33.9 | 5.69 | 4.98 | 26.7 | 28.5 | 12.5 | 0.34 |
| 1-1/4 | 3HS20SW | 42.7 | 6.07 | 5.28 | 35.1 | 30.0 | 12.5 | 0.48 |
| 1-1/2 | 3HS24SW | 48.8 | 6.35 | 5.54 | 40.9 | 32.0 | 12.5 | 0.56 |
| 2 | 3HS32SW | 61.2 | 6.93 | 6.04 | 52.5 | 41.0 | 16 | 1.09 |

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Half Couplings are available in BSPT, BSPP, NPT and Socket Weld configurations

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799

Larger sizes are available upon request

Couplings can also be supplied as part of our low pressure 150lb range



We also keep Half Couplings in BSPT, BSPP and NPT thread types in 3000lb 316/L

