



SIZE BSPP (G1)	SIZE BSPP (G2)	PRODUCT CODE	PRESSURE (BAR)	A	B	C	D	E	F	HEX 1	HEX 2	KG EACH
1/8	1/8	FSP02	350	30.2	13.1	8.1	3.5	4.1	3.5	19.1	14.3	0.03
1/4	1/4	FSP04	350	37.2	15.1	11.1	4.7	4.2	4.7	19.1	18.1	0.05
3/8	3/8	FSP06	350	41.7	16.5	12.1	8.1	4.6	8.1	22.2	22.2	0.09
1/2	1/2	FSP08	315	47.3	16.5	14.1	11.1	6.8	11.1	28.6	25.6	0.15
3/4	3/4	FSP12	250	52.6	17.5	16.1	16.6	8.7	16.6	31.7	31.7	0.21
1	1	FSP16	200	62.2	21.2	19.1	22.2	10.1	22.2	41.3	38.1	0.35
1-1/4	1-1/4	FSP20	160	66.4	21.5	20.1	28.5	10.5	28.5	50.8	47.2	0.55
1-1/2	1-1/2	FSP24	125	87.8	26.4	22.1	33.3	12.2	33.3	56.4	56.4	0.78
2	2	FSP32	80	103.1	30.1	25.1	46.1	15.1	46.1	69.8	69.8	1.04

**** DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL ****

NERO's range of Swivel Adaptors are available in BSPP x BSPP threads, with a 60° internal cone on the Female Swivel end and BSPP the other in a Male thread

Pressure rating up to 350 BAR (size dependant)

Can be supplied with 2.2 Certificate if Conformity - upon request

BSPP Female thread are to ISO 228/1
60° internal cone to BS 5200

We also keep a BSPT Male version of this fitting + Bonded Washers in our Hydraulic range



We stock a wide range of Hydraulic Fittings to suit your requirements



5 STAR ★★★★★ CUSTOMER SERVICE



SAME DAY DISPATCH - ORDERS PLACED BEFORE 4:30PM



WEALTH OF INDUSTRY KNOWLEDGE



ONE OF THE LARGEST STOCKISTS IN THE UK