



SIZE	PRODUCT CODE	DIMENSIONS		KG EACH
		A	B	
1/4 x 1/8	3RS0402SW	22	25	0.05
3/8 x 1/4	3RS0604SW	25	25	0.06
1/2 x 1/4	3RS0804SW	31	29	0.13
1/2 x 3/8	3RS0806SW	31	29	0.13
3/4 x 3/8	3RS1206SW	36	35	0.18
3/4 x 1/2	3RS1208SW	36	35	0.18
1 x 1/2	3RS1608SW	45	38	0.26
1 x 3/4	3RS1612SW	45	38	0.26
1-1/4 x 1	3RS2016SW	55	38	0.48
1-1/2 x 1	3RS2416SW	60	38	0.57
1-1/2 x 1-1/4	3RS2420SW	60	38	0.57
2 x 1	3RS3216SW	75	51	1.50
2 x 1-1/4	3RS3220SW	75	51	0.98
2 x 1-1/2	3RS3224SW	75	51	0.92

**\*\* DIMENSIONS SUBJECT TO CHANGE - PLEASE CONTACT US IF CRITICAL \*\***

NERO's range of Reducing Couplings are available in NPT and Socket Weld configurations

Pressure rating up to 200 BAR (3000 PSI)

Full Material traceability is available and 3.1B certification can be provided upon request

Socket Weld ends are to ASME B16.11-2016 / BS3799

Larger sizes are available upon request

Reducing Couplings in BSPP, NPT and Socket Weld can also be supplied as part of our low pressure 150lb range



We also keep Reducing Couplings in NPT 3000# 316/L

